

Package ‘pacbpred’

February 20, 2015

Type Package

Title PAC-Bayesian Estimation and Prediction in Sparse Additive Models.

Version 0.92.2

Date 2013-02-05

Author Benjamin Guedj

Maintainer Benjamin Guedj <benjamin.guedj@upmc.fr>

Description This package is intended to perform estimation and prediction in high-dimensional additive models, using a sparse PAC-Bayesian point of view and a MCMC algorithm. The method is fully described in Guedj and Alquier (2013), 'PAC-Bayesian Estimation and Prediction in Sparse Additive Models', Electronic Journal of Statistics, 7, 264--291.

License GPL (>= 2)

URL <http://www.lsta.upmc.fr/doct/guedj/index.html>

Repository CRAN

Date/Publication 2013-02-05 13:41:35

NeedsCompilation no

R topics documented:

pacbpred-package	2
pacbpred	3

Index	6
--------------	----------

pacbpred-package

PAC-Bayesian Estimation and Prediction in Sparse Additive Models

Description

This package is intended to perform estimation and prediction in high-dimensional additive models, using a PAC-Bayesian point of view and a MCMC algorithm.

Details

Package: pacbpred
Type: Package
Version: 0.92.2
Date: 2013-02-05
License: GPL (>= 2)

Author(s)

Benjamin Guedj

Maintainer: Benjamin Guedj <benjamin.guedj@upmc.fr>

References

<http://www.lsta.upmc.fr/doct/guedj/index.html>

Guedj and Alquier (2013), 'PAC-Bayesian Estimation and Prediction in Sparse Additive Models'. *Electronic Journal of Statistics*, 7, 264–291. DOI:10.1214/13-EJS771. Available on <http://projecteuclid.org/DPubS?service=UI&version=1.0&verb=Display&handle=euclid.ejs/1359041592>.

See Also

pacbpred

Examples

```
ndata <- 100
ntrain <- 80
ntest <- ndata - ntrain
p <- 10
Y <- numeric(ndata)
X <- matrix(nr = ndata, nc = p, data = 2*runif(n = ndata*p) - 1)
for(i in 1:ndata)
{
  Y[i] <- X[i,1]^3+sin(pi*X[i,2])
}
```

```

Xtrain <- X[1:ntrain,]
Xtest <- X[(ntrain+1):ndata,]
Ytrain <- Y[1:ntrain]
Ytest <- Y[(ntrain+1):ndata]

niter <- 100
cst <- Inf
alpha <- .1
sigma2 <- .1
delta <- ntrain/2

res <- pacbpred(niter = niter, Xtrain = Xtrain, Xtest = Xtest, Y =
Ytrain, cst = cst,
sigma2 = sigma2, delta = delta, alpha = alpha)

print(cbind(res$predict,Ytest))

```

pacbpred

pacbpred

Description

This package is intended to perform estimation and prediction in high-dimensional additive models, using a PAC-Bayesian point of view and a MCMC algorithm. The method is fully described in Guedj and Alquier (2013), 'PAC-Bayesian Estimation and Prediction in Sparse Additive Models', see <http://projecteuclid.org/DPubS?service=UI&version=1.0&verb=Display&handle=euclid.ejs/1359041592>.

Usage

```

pacbpred(niter, burnin = floor(niter * 2/3), Xtrain, Xtest, Y, K = 8,
cst,
sigma2, alpha = 0.1, delta)

```

Arguments

niter	Mandatory. The number of MCMC iterations.
burnin	Optional. How many iterations should be discarded in the beginning of the chain?
Xtrain	Mandatory. The design matrix of the training sample.
Xtest	Optional. The design matrix of the test sample.
Y	Mandatory. The vector of responses corresponding to Xtrain. Y is assumed to have the same number of rows as Xtrain.
K	Optional. The maximal order of the development on the trigonometric basis.

cst	Optional. A numerical constant bounding from above the sup norm of true regression function.
sigma2	Optional. The variance of the proposal density along the algorithm.
alpha	Optional. The penalization term over the complexity of a model.
delta	Optional. The inverse temperature parameter.

Details

See Guedj and Alquier (2013), 'PAC-Bayesian Estimation and Prediction in Sparse Additive Models' on <http://projecteuclid.org/DPubS?service=UI&version=1.0&verb=Display&handle=euclid.ejs/1359041592>.

Value

A list composed of the following items.

predict	If <code>Xtest</code> is provided, the predicted values of the corresponding responses.
estimates	The vector of estimates over the trigonometric basis.
ratio.mcmc	A vector of the MCMC ratio for each iteration.
accept	A logical vector whose length is the number of iterations. For each iteration, has the proposed move been accepted ?
models.mcmc	The current models all along the MCMC chain.

Note

This is still an early stage development. Use at your own risk !

Author(s)

Benjamin Guedj

References

<http://www.lsta.upmc.fr/doct/guedj/index.html>

Guedj and Alquier (2013), 'PAC-Bayesian Estimation and Prediction in Sparse Additive Models'. *Electronic Journal of Statistics*, 7, 264–291. DOI:10.1214/13-EJS771. Available on <http://projecteuclid.org/DPubS?service=UI&version=1.0&verb=Display&handle=euclid.ejs/1359041592>.

See Also

`pacbpred-package`

Examples

```
ndata <- 100
ntrain <- 80
ntest <- ndata - ntrain
p <- 10
Y <- numeric(ndata)
X <- matrix(nr = ndata, nc = p, data = 2*runif(n = ndata*p) - 1)
for(i in 1:ndata)
  {
    Y[i] <- X[i,1]^3+sin(pi*X[i,2])
  }

Xtrain <- X[1:ntrain,]
Xtest <- X[(ntrain+1):ndata,]
Ytrain <- Y[1:ntrain]
Ytest <- Y[(ntrain+1):ndata]

niter <- 100
cst <- Inf
alpha <- .1
sigma2 <- .1
delta <- ntrain/2

res <- pacbpred(niter = niter, Xtrain = Xtrain, Xtest = Xtest, Y =
Ytrain, cst = cst,
sigma2 = sigma2, delta = delta, alpha = alpha)

print(cbind(res$predict,Ytest))
```

Index

- *Topic **nonlinear**
 - [pacbpred, 3](#)
 - *Topic **pac-bayesian**
 - [pacbpred, 3](#)
 - *Topic **package**
 - [pacbpred-package, 2](#)
 - *Topic **prediction**
 - [pacbpred, 3](#)
- [pacbpred, 3](#)
[pacbpred-package, 2](#)